



# FAP\*T Economy Attenuators

\*Available in: 3dB, 6dB, 8dB, 10dB, 12dB, 16dB & 20dB



The RMS FAP attenuators have been designed and manufactured to the highest standards. They are ideal for all applications from the drop to the headend. The standard values are \*3dB, 6dB, 8dB, 10dB, 12dB, 16dB & 20dB

## Features:

- Bandwidth 5MHz to 1GHz
- RFI Shielding >-120dB
- Solid screw machined brass, silver plated body.
- Precision machined #22 gauge center pin
- Precision machined "F" ports that are SCTE compliant
- Non power passing
- Laminated label with dB value clearly marked
- 360 degree center conductor contact seizure provides high holding force, and excellent wiping action.
- F61 designed to accept RG6 or RG59 cables
- Very flat attenuation & excellent return loss
- Light weight, compact size, easy to install
- CE approved

### Specifications FAP\* Attenuators

Model Number --->	FAP3T	FAP6T	FAP8T	FAP10T	FAP12T	FAP16T	FAP20T
Attenuation value ---->	3dB	6dB	8dB	10dB	12dB	16dB	20dB
Attenuation Loss							
5 - 1000MHz	3.2	6	8	10	12	15.5	20
Tolerance	+5%	+5%	+5%	+5%	+5%	+5%	+5%
Return Loss Minimum							
5 - 500MHz	20	20	20	20	20	20	20
500 - 1000MHz	18	18	18	18	18	18	18
Dimensions	1-1/4" L X 7/16" W (31.7mm L X 11.1mm W)						

\* Specify dB value

RMS Communications Inc

11516 Downs Road, Pineville, North Carolina. 28134 USA  
Toll Free: 1-800-223-8312 - Phone (704) 588-4008